



Rocker Lug caps for Fire Safe Female Coupling Caps With Chain

Our Product Introduction

Basic Information

- Place of Origin: CHINA
- Brand Name: DEYE
- Certification: ISO9001:2015 PED
- Model Number: DY-QC-23
- Minimum Order Quantity: 10PCS
- Price: USD2-USD25 each
- Packaging Details: carton box+ ply wooden cases or carton+ Pallets
- Delivery Time: 20 days for usual order, 7 days for stocked items
- Payment Terms: T/T, L/C, D/P
- Supply Ability: 1000pcs one month



Product Specification

- Highlight: Vessel Camlock Quick Couplings, Aluminum Camlock Quick Couplings, stainless steel camlock connectors

Product Description

Rocker Lug caps for Fire Safe Female Coupling Caps With Chain

Brass fire hose and hydrant caps provide good strength, ductility, and corrosion resistance. They are more heat-resistant than aluminum fire hose and hydrant caps. They twist onto fire hydrant and hose openings to keep out dirt and prevent damage to external threads. Fire hose and hydrant caps and plugs are accessories that protect the open ends of hydrants and hoses when not in use. Caps cover fire hydrant and hose openings to keep out dirt and prevent damage to external threads. Plugs screw into hydrant or hose openings to cover and protect both internal and external threads from dirt and damage. Some caps and plugs come with a chain that connects the fitting to the hydrant or hose to prevent it from getting lost.

Product Information/Product Description/Basis Information/Specification

Item	Hydrant Cap
Tightening Method	Rocker Lug
Hose Fitting Gender	Female/ Male
Color	Gold
Breakable	No
Includes Chain	Yes
Material	Brass
Compatible Pipe Size	Male Adapter, 1" 1 1/2 in, 2", 2-1/2in, 3in, 4in, 5in, 6in, Hose Fittings: 1-3/4" 3"
Thread Type	NH/ NST
Includes	Rocker Lug

Features /Advantages:

1. Simple structure, convenient operation, quick connect and open it
2. compact size, light weight, good sealing and interchangeability
3. Adapt to all kinds of working conditions, widely used in liquid, powder and other medium
4. Joint connected with taper pipe threads, outside taper pipe threads, intubation connection, flange connection, etc
5. Cam & groove couplings are easy to operate. Camlock consists of two parts - male adapter and female coupler. You just need insert the adapter into the coupler until contact is made with the gasket. Then press down the cam arms simultaneously to produce a uniform gasket compression. During the process of installation, no tools are required and hand pressure is enough. Hence, camlock fittings not only save your time but also the tools and human power
6. Cam & groove couplings are equipped with PVC suction hoses, lay flat discharge hoses and other low-pressure hoses. It can simplify the operation and save working time greatly. However, cam locks are not suitable for any kind of hose. It is forbidden to be used in compressed air or gas or high-pressure applications

Application and usage

Quick release coupling for low-pressure systems, Suitable for Construction; Fire hydrant; Garden; Farming

Our Service

1. Technical support
2. Raw Material Quality control.
3. Inspection during the production time.
4. Final Test includes Surface, Dimension, PT Test, RT test, ultrasonic Test
5. Test Report each shipment
4. Flexible Delivery terms. EXW FOB CIF CFR DDP DDU
5. Flexible payment Ways: LC. TT. DP
6. Customized Package includes Logo. Cases Dimension.
7. 18 months quality Guarantee time.
9. Free replacement by air if any error founded
10. 24 hours to Feedback your questions

DEYE SHIJIAZHUANG DEYE PIPING INDUSTRY CO., LTD Pipefittings Department)



+8613292824811



sales@deyepiping.com



piping-industry.com

No. 368 Youyi St. Shijiazhuang, Hebei, China